

## 100TH GENERAL ASSEMBLY State of Illinois 2017 and 2018 HB5540

by Rep. Jerry Lee Long

## SYNOPSIS AS INTRODUCED:

625 ILCS 5/15-107

from Ch. 95 1/2, par. 15-107

Amends the Illinois Vehicle Code. Repeals provisions providing that the distance between the kingpin and the center axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 42 feet 6 inches and that such a limit shall not apply to trailers or semitrailers used for the transport of livestock.

LRB100 18065 LNS 33256 b

1 AN ACT concerning transportation.

## Be it enacted by the People of the State of Illinois, represented in the General Assembly:

- Section 5. The Illinois Vehicle Code is amended by changing

  Section 15-107 as follows:
- 6 (625 ILCS 5/15-107) (from Ch. 95 1/2, par. 15-107)
- 7 Sec. 15-107. Length of vehicles.
- 8 (a) The maximum length of a single vehicle on any highway 9 of this State may not exceed 42 feet except the following:
- 10 (1) Semitrailers.
- 11 (2) Charter or regulated route buses may be up to 45 12 feet in length, not including energy absorbing bumpers.
- 13 (a-1) A motor home as defined in Section 1-145.01 may be up 14 to 45 feet in length, not including energy absorbing bumpers. 15 The length limitations described in this subsection (a-1) shall
- 16 be exclusive of energy-absorbing bumpers and rear view mirrors.
- 17 (b) On all non-State highways, the maximum length of vehicles in combinations is as follows:
- 19 (1) A truck tractor in combination with a semitrailer
  20 may not exceed 65 feet overall dimension. An agency or
  21 instrumentality of the State of Illinois or any unit of
  22 local government shall not be required to widen or
  23 otherwise alter a non-State highway constructed before the

effective date of this amendatory Act of the 100th General
Assembly to accommodate truck tractors under this
paragraph (1).

- (2) A truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer may not exceed 60 feet overall dimension.
- (3) Combinations specially designed to transport motor vehicles or boats may not exceed 60 feet overall dimension.
- (4) (Blank). The distance between the kingpin and the center axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 42 feet 6 inches. The limit contained in this paragraph (4) shall not apply to trailers or semitrailers used for the transport of livestock as defined by Section 18b-101.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismembered are exempt from length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

Vehicles and loads operated by a public utility while en

1	route to make emergency repairs to public service facilities or
2	properties are exempt from length limitations, provided that
3	during night operations every vehicle and its load must be
4	equipped with a sufficient number of clearance lamps on both
5	sides and marker lamps on the extreme ends of any projecting
6	load to clearly mark the dimensions of the load.

A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

All other combinations not listed in this subsection (b)
may not exceed 60 feet overall dimension.

- (c) Except as provided in subsections (c-1) and (c-2), combinations of vehicles may not exceed a total of 2 vehicles except the following:
  - (1) A truck tractor semitrailer may draw one trailer.
  - (2) A truck tractor semitrailer may draw one converter dolly or one semitrailer.
  - (3) A truck tractor semitrailer may draw one vehicle that is defined in Chapter 1 as special mobile equipment, provided the overall dimension does not exceed 60 feet.
  - (4) A truck in transit may draw 3 trucks in transit coupled together by the triple saddlemount method.
  - (5) Recreational vehicles consisting of 3 vehicles, provided the following:
    - (A) The total overall dimension does not exceed 60

25

26

1	feet.
2	(B) The towing vehicle is a properly registered
3	vehicle capable of towing another vehicle using a
4	fifth-wheel type assembly.
5	(C) The second vehicle in the combination of
6	vehicles is a recreational vehicle that is towed by a
7	fifth-wheel assembly. This vehicle must be properly
8	registered and must be equipped with brakes,
9	regardless of weight.
10	(D) The third vehicle must be the lightest of the 3
11	vehicles and be a trailer or semitrailer designed or
12	used for transporting a boat, all-terrain vehicle,
13	personal watercraft, or motorcycle.
14	(E) The towed vehicles may be only for the use of
15	the operator of the towing vehicle.
16	(F) All vehicles must be properly equipped with
17	operating brakes and safety equipment required by this
18	Code, except the additional brake requirement in
19	subdivision (C) of this subparagraph (5).
20	(6) A tow truck in combination with a disabled vehicle
21	or combination of disabled vehicles, provided the towing
22	vehicle:
23	(A) Is specifically designed as a tow truck having

a gross vehicle weight rating of at least 18,000 pounds

and equipped with air brakes, provided that air brakes

are required only if the towing vehicle is towing a

vehicle, semitrailer, or tractor-trailer combination that is equipped with air brakes. For the purpose of this subsection, gross vehicle weight rating, or GVWR, means the value specified by the manufacturer as the loaded weight of the tow truck.

- (B) Is equipped with flashing, rotating, or oscillating amber lights, visible for at least 500 feet in all directions.
- (C) Is capable of utilizing the lighting and braking systems of the disabled vehicle or combination of vehicles.
- (D) Does not engage a tow exceeding 50 highway miles from the initial point of wreck or disablement to a place of repair. Any additional movement of the vehicles may occur only upon issuance of authorization for that movement under the provisions of Sections 15-301 through 15-319 of this Code.

The Department may by rule or regulation prescribe additional requirements regarding length limitations for a tow truck towing another vehicle.

For purposes of this Section, a tow-dolly that merely serves as substitute wheels for another legally licensed vehicle is considered part of the licensed vehicle and not a separate vehicle.

(7) Commercial vehicles consisting of 3 vehicles, provided the following:

1	(A) The total overall dimension does not exceed 65
2	feet.
3	(B) The towing vehicle is a properly registered
4	vehicle capable of towing another vehicle using a
5	fifth-wheel type assembly or a goose-neck hitch ball.
6	(C) The third vehicle must be the lightest of the 3
7	vehicles and be a trailer or semitrailer.
8	(D) All vehicles must be properly equipped with
9	operating brakes and safety equipment required by this
-0	Code.
1	(E) The combination of vehicles must be operated by
_2	a person who holds a commercial driver's license (CDL).
13	(F) The combination of vehicles must be en route to
4	a location where new or used trailers are sold by an
.5	Illinois or out-of-state licensed new or used trailer
6	dealer.
_7	(c-1) A combination of 3 vehicles is allowed access to any
8_8	State designated highway if:
_9	(1) the length of neither towed vehicle exceeds 28.5
20	feet;
21	(2) the overall wheel base of the combination of
22	vehicles does not exceed 62 feet; and
23	(3) the combination of vehicles is en route to a
24	location where new or used trailers are sold by an Illinois
25	or out-of-state licensed new or used trailer dealer.

26 (c-2) A combination of 3 vehicles is allowed access from

1	any State designated highway onto any county, township, o
2	municipal highway for a distance of 5 highway miles for the
3	purpose of delivery or collection of one or both of the tower
4	vehicles if:

- (1) the length of neither towed vehicle exceeds 28.5 feet;
  - (2) the combination of vehicles does not exceed 40,000 pounds in gross weight and 8 feet 6 inches in width;
    - (3) there is no sign prohibiting that access;
  - (4) the route is not being used as a thoroughfare between State designated highways; and
  - (5) the combination of vehicles is en route to a location where new or used trailers are sold by an Illinois or out-of-state licensed new or used trailer dealer.
  - (d) On Class I highways there are no overall length limitations on motor vehicles operating in combinations provided:
    - (1) The length of a semitrailer, unladen or with load, in combination with a truck tractor may not exceed 53 feet.
    - (2) (Blank). The distance between the kingpin and the center of the rear axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 45 feet 6 inches. The limit contained in this paragraph (2) shall not apply to trailers or semi-trailers used for the transport of livestock as defined by Section 18b-101.
      - (3) The length of a semitrailer or trailer, unladen or

with load, operated in a truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination, may not exceed 28 feet 6 inches.

- (4) Maxi-cube combinations, as defined in Chapter 1, may not exceed 65 feet overall dimension.
- (5) Combinations of vehicles specifically designed to transport motor vehicles or boats may not exceed 65 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
- (6) Stinger-steered semitrailer vehicles specifically designed to transport motor vehicles or boats and automobile transporters, as defined in Chapter 1, may not exceed 80 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
- (7) A truck in transit transporting 3 trucks coupled together by the triple saddlemount method may not exceed 97 feet overall dimension.
- (8) A towaway trailer transporter combination may not exceed 82 feet overall dimension.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismembered are exempt from

length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.

A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

The length limitations described in this paragraph (d) shall be exclusive of safety and energy conservation devices, such as bumpers, refrigeration units or air compressors and other devices, that the Department may interpret as necessary for safe and efficient operation; except that no device excluded under this paragraph shall have by its design or use the capability to carry cargo.

1	Section	5-35 of the	: Illinois	Administrat	cive	Procedu	ıre	Act
2	relating to	procedures	for rulem	aking shall	not	apply	to	the
3	designation	of highways	under this	s paragraph	(d).			

- (e) On Class II highways there are no overall length limitations on motor vehicles operating in combinations, provided:
  - (1) The length of a semitrailer, unladen or with load, in combination with a truck tractor, may not exceed 53 feet overall dimension.
  - (2) (Blank). The distance between the kingpin and the center of the rear axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 45 feet 6 inches. The limit contained in this paragraph (2) shall not apply to trailers or semi-trailers used for the transport of livestock as defined by Section 18b-101.
  - (3) A truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination may not exceed 65 feet in dimension from front axle to rear axle.
  - (4) The length of a semitrailer or trailer, unladen or with load, operated in a truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination, may not exceed 28 feet 6 inches.
  - (5) Maxi-cube combinations, as defined in Chapter 1, may not exceed 65 feet overall dimension.
  - (6) A combination of vehicles, specifically designed to transport motor vehicles or boats, may not exceed 65

feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.

- (7) Stinger-steered semitrailer vehicles specifically designed to transport motor vehicles or boats may not exceed 80 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
- (8) A truck in transit transporting 3 trucks coupled together by the triple saddlemount method may not exceed 97 feet overall dimension.
- (9) A towaway trailer transporter combination may not exceed 82 feet overall dimension.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismembered are exempt from length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.

A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

Local authorities, with respect to streets and highways under their jurisdiction, may also by ordinance or resolution allow length limitations of this subsection (e).

The length limitations described in this paragraph (e) shall be exclusive of safety and energy conservation devices, such as bumpers, refrigeration units or air compressors and other devices, that the Department may interpret as necessary for safe and efficient operation; except that no device excluded under this paragraph shall have by its design or use the capability to carry cargo.

Section 5-35 of the Illinois Administrative Procedure Act relating to procedures for rulemaking shall not apply to the designation of highways under this paragraph (e).

(e-1) Combinations of vehicles not exceeding 65 feet overall length are allowed access as follows:

1	(1) From any State designated highway onto any county,
2	township, or municipal highway for a distance of 5 highway
3	miles for the purpose of loading and unloading, provided:
4	(A) The vehicle does not exceed 80.000 pounds in

- (A) The vehicle does not exceed 80,000 pounds in gross weight and 8 feet 6 inches in width.
  - (B) There is no sign prohibiting that access.
- (C) The route is not being used as a thoroughfare between State designated highways.
- (2) From any State designated highway onto any county or township highway for a distance of 5 highway miles or onto any municipal highway for a distance of one highway mile for the purpose of food, fuel, repairs, and rest, provided:
  - (A) The vehicle does not exceed 80,000 pounds in gross weight and 8 feet 6 inches in width.
    - (B) There is no sign prohibiting that access.
  - (C) The route is not being used as a thoroughfare between State designated highways.
- (e-2) Except as provided in subsection (e-3), combinations of vehicles over 65 feet in length, with no overall length limitation except as provided in subsections (d) and (e) of this Section, are allowed access as follows:
  - (1) From a Class I highway onto any street or highway for a distance of one highway mile for the purpose of loading, unloading, food, fuel, repairs, and rest, provided there is no sign prohibiting that access.

- 1 (2) From a Class I or Class II highway onto any State 2 highway or any locally designated highway for a distance of 3 5 highway miles for the purpose of loading, unloading, 4 food, fuel, repairs, and rest.
  - (e-3) Combinations of vehicles over 65 feet in length operated by household goods carriers or towaway trailer transporter combinations, with no overall length limitations except as provided in subsections (d) and (e) of this Section, have unlimited access to points of loading, unloading, or delivery to or from a manufacturer, distributor, or dealer.
  - (f) On Class III and other non-designated State highways, the length limitations for vehicles in combination are as follows:
    - (1) Truck tractor-semitrailer combinations must comply with a maximum 65 feet extreme overall dimension. An agency or instrumentality of the State of Illinois or any unit of local government shall not be required to widen or otherwise alter a Class III or other non-designated State highway constructed before the effective date of this amendatory Act of the 100th General Assembly to accommodate truck tractor-semitrailer combinations under this paragraph (1).
    - (2) Semitrailers, unladen or with load, may not exceed53 feet overall dimension.
    - (3) No truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination may exceed 60

feet extreme overall dimension.

- (4) (Blank). The distance between the kingpin and the center axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 42 feet 6 inches. The limit contained in this paragraph (4) shall not apply to trailers or semi trailers used for the transport of livestock as defined by Section 18b 101.
- (g) Length limitations in the preceding subsections of this Section 15-107 do not apply to the following:
  - (1) Vehicles operated in the daytime, except on Saturdays, Sundays, or legal holidays, when transporting poles, pipe, machinery, or other objects of a structural nature that cannot readily be dismembered, provided the overall length of vehicle and load may not exceed 100 feet and no object exceeding 80 feet in length may be transported unless a permit has been obtained as authorized in Section 15-301.
  - (2) Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties, but during night operation every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps upon the extreme ends of any projecting load to clearly mark the dimensions of the load.
  - (3) A tow truck in combination with a disabled vehicle or combination of disabled vehicles, provided the towing

vehicle meets the following conditions:

- (A) It is specifically designed as a tow truck having a gross vehicle weight rating of at least 18,000 pounds and equipped with air brakes, provided that air brakes are required only if the towing vehicle is towing a vehicle, semitrailer, or tractor-trailer combination that is equipped with air brakes.
  - (B) It is equipped with flashing, rotating, or oscillating amber lights, visible for at least 500 feet in all directions.
  - (C) It is capable of utilizing the lighting and braking systems of the disabled vehicle or combination of vehicles.
- (D) It does not engage in a tow exceeding 50 miles from the initial point of wreck or disablement.

The Department may by rule or regulation prescribe additional requirements regarding length limitations for a tow truck towing another vehicle. The towing vehicle, however, may tow any disabled vehicle from the initial point of wreck or disablement to a point where repairs are actually to occur. This movement shall be valid only on State routes. The tower must abide by posted bridge weight limits.

For the purpose of this subsection, gross vehicle weight rating, or GVWR, shall mean the value specified by the manufacturer as the loaded weight of the tow truck. Legal holidays referred to in this Section shall be specified as the

- day on which the following traditional holidays are celebrated:
- 2 New Year's Day;
- 3 Memorial Day;
- 4 Independence Day;
- 5 Labor Day;

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

- 6 Thanksgiving Day; and
- 7 Christmas Day.
  - (h) The load upon any vehicle operated alone, or the load upon the front vehicle of a combination of vehicles, shall not extend more than 3 feet beyond the front wheels of the vehicle or the front bumper of the vehicle if it is equipped with a front bumper. The provisions of this subsection (h) shall not apply to any vehicle or combination of vehicles specifically designed for the collection and transportation of waste, or recyclable materials during the vehicle's operation in the course of collecting garbage, waste, or recyclable materials if the vehicle is traveling at a speed not in excess of 15 miles per hour during the vehicle's operation and in the course of collecting garbage, waste, or recyclable materials. However, in no instance shall the load extend more than 7 feet beyond the front wheels of the vehicle or the front bumper of the vehicle if it is equipped with a front bumper.
    - (i) The load upon the front vehicle of an automobile transporter or a stinger-steered vehicle specifically designed to transport motor vehicles shall not extend more than 4 feet beyond the foremost part of the transporting vehicle and the

- 1 load upon the rear transporting vehicle shall not extend more
- 2 than 6 feet beyond the rear of the bed or body of the vehicle.
- 3 This paragraph shall only be applicable upon highways
- 4 designated in paragraphs (d) and (e) of this Section.
- 5 (j) Articulated vehicles comprised of 2 sections, neither
- 6 of which exceeds a length of 42 feet, designed for the carrying
- of more than 10 persons, may be up to 60 feet in length, not
- 8 including energy absorbing bumpers, provided that the vehicles
- 9 are:
- 1. operated by or for any public body or motor carrier
- 11 authorized by law to provide public transportation
- 12 services; or
- 13 2. operated in local public transportation service by
- any other person and the municipality in which the service
- is to be provided approved the operation of the vehicle.
- 16 (j-1) (Blank).
- 17 (k) Any person who is convicted of violating this Section
- is subject to the penalty as provided in paragraph (b) of
- 19 Section 15-113.
- 20 (1) (Blank).
- 21 (Source: P.A. 99-717, eff. 8-5-16; 100-201, eff. 8-18-17;
- 22 100-343, eff. 1-1-18.)