

1 AN ACT in relation to vehicles.

2 Be it enacted by the People of the State of Illinois,
3 represented in the General Assembly:

4 Section 5. The Illinois Vehicle Code is amended by
5 changing Section 15-111 as follows:

6 (625 ILCS 5/15-111) (from Ch. 95 1/2, par. 15-111)
7 Sec. 15-111. Wheel and axle loads and gross weights.

8 (a) On non-designated highways, no vehicle or
9 combination of vehicles equipped with pneumatic tires may be
10 operated, unladen or with load, when the total weight
11 transmitted to the road surface exceeds 18,000 pounds on a
12 single axle or 32,000 pounds on a tandem axle with no axle
13 within the tandem exceeding 18,000 pounds except:

14 (1) when a different limit is established and
15 posted in accordance with Section 15-316 of this Code;

16 (2) vehicles for which the Department of
17 Transportation and local authorities issue overweight
18 permits under authority of Section 15-301 of this Code;

19 (3) tow trucks subject to the conditions provided
20 in subsection (d) may not exceed 24,000 pounds on a
21 single rear axle or 44,000 pounds on a tandem rear axle;

22 (4) any single axle of a 2-axle truck weighing
23 36,000 pounds or less and not a part of a combination of
24 vehicles, shall not exceed 20,000 pounds;

25 (5) any single axle of a 2-axle truck equipped with
26 a personnel lift or digger derrick, weighing 36,000
27 pounds or less, owned and operated by a public utility,
28 shall not exceed 20,000 pounds;

29 (6) any single axle of a 2-axle truck specially
30 equipped with a front loading compactor used exclusively
31 for garbage, refuse, or recycling may not exceed 20,000

1 pounds per axle, provided that the gross weight of the
2 vehicle does not exceed 40,000 pounds;

3 (7) a truck, not in combination and specially
4 equipped with a selfcompactor or an industrial roll-off
5 hoist and roll-off container, used exclusively for
6 garbage or refuse operations may, when laden, transmit
7 upon the road surface the following maximum weights:
8 22,000 pounds on a single axle; 40,000 pounds on a tandem
9 axle;

10 (8) a truck, not in combination and used
11 exclusively for the collection of rendering materials,
12 may, when laden, transmit upon the road surface the
13 following maximum weights: 22,000 pounds on a single
14 axle; 40,000 pounds on a tandem axle;

15 (9) tandem axles on a 3-axle truck registered as a
16 Special Hauling Vehicle, manufactured prior to or in the
17 model year of 2014 2004 and first registered in Illinois
18 prior to January 1, 2015 2005, with a distance greater
19 than 72 inches but not more than 96 inches between any
20 series of 2 axles, is allowed a combined weight on the
21 series not to exceed 36,000 pounds and neither axle of
22 the series may exceed 18,000 pounds. Any vehicle of this
23 type manufactured after the model year of 2014 2004 or
24 first registered in Illinois after December 31, 2014 2004
25 may not exceed a combined weight of 32,000 pounds through
26 the series of 2 axles and neither axle of the series may
27 exceed 18,000 pounds;

28 (10) tandem axles on a 4-axle truck mixer, whose
29 fourth axle is a road surface engaging mixer trailing
30 axle, registered as a Special Hauling Vehicle, used
31 exclusively for the mixing and transportation of concrete
32 and manufactured prior to or in the model year of 2014
33 2004 and first registered in Illinois prior to January 1,
34 2015 2005, with a distance greater than 72 inches but not

1 more than 96 inches between any series of 2 axles, is
 2 allowed a combined weight on the series not to exceed
 3 36,000 pounds and neither axle of the series may exceed
 4 18,000 pounds. Any vehicle of this type manufactured
 5 after the model year of 2014 ~~2004~~ or first registered in
 6 Illinois after December 31, 2014 ~~2004~~ may not exceed a
 7 combined weight of 32,000 pounds through the series of 2
 8 axles and neither axle of the series may exceed 18,000
 9 pounds;

10 (11) 4-axle vehicles or a 5 or more axle
 11 combination of vehicles: The weight transmitted upon the
 12 road surface through any series of 3 axles whose centers
 13 are more than 96 inches apart, measured between extreme
 14 axles in the series, may not exceed those allowed in the
 15 table contained in subsection (f) of this Section. No
 16 axle or tandem axle of the series may exceed the maximum
 17 weight permitted under this Section for a single or
 18 tandem axle.

19 No vehicle or combination of vehicles equipped with other
 20 than pneumatic tires may be operated, unladen or with load,
 21 upon the highways of this State when the gross weight on the
 22 road surface through any wheel exceeds 800 pounds per inch
 23 width of tire tread or when the gross weight on the road
 24 surface through any axle exceeds 16,000 pounds.

25 (b) On non-designated highways, the gross weight of
 26 vehicles and combination of vehicles including the weight of
 27 the vehicle or combination and its maximum load shall be
 28 subject to the foregoing limitations and further shall not
 29 exceed the following gross weights dependent upon the number
 30 of axles and distance between extreme axles of the vehicle or
 31 combination measured longitudinally to the nearest foot.

32 VEHICLES HAVING 2 AXLES 36,000 pounds

33 VEHICLES OR COMBINATIONS

1		HAVING 3 AXLES		
2	With Tandem		With or	
3	Axles		Without	
4			Tandem Axles	
5	Minimum		Minimum	
6	distance to	Maximum	distance to	Maximum
7	nearest foot	Gross	nearest foot	Gross
8	between	Weight	between	Weight
9	extreme axles	(pounds)	extreme axles	(pounds)
10	10 feet	41,000	16 feet	46,000
11	11	42,000	17	47,000
12	12	43,000	18	47,500
13	13	44,000	19	48,000
14	14	44,500	20	49,000
15	15	45,000	21 feet or more	50,000

VEHICLES OR COMBINATIONS

17		HAVING 4 AXLES		
18	Minimum		Minimum	
19	distance to	Maximum	distance to	Maximum
20	nearest foot	Gross	nearest foot	Gross
21	between	Weight	between	Weight
22	extreme axles	(pounds)	extreme axles	(pounds)
23	15 feet	50,000	26 feet	57,500
24	16	50,500	27	58,000
25	17	51,500	28	58,500
26	18	52,000	29	59,500
27	19	52,500	30	60,000
28	20	53,500	31	60,500
29	21	54,000	32	61,500
30	22	54,500	33	62,000
31	23	55,500	34	62,500
32	24	56,000	35	63,500
33	25	56,500	36 feet or more	64,000

34 A vehicle not in a combination having more than 4 axles

1 may not exceed the weight in the table in this subsection (b)
2 for 4 axles measured between the extreme axles of the
3 vehicle.

4 COMBINATIONS HAVING 5 OR MORE AXLES

5	Minimum distance to	Maximum
6	nearest foot between	Gross Weight
7	extreme axles	(pounds)
8	42 feet or less	72,000
9	43	73,000
10	44 feet or more	73,280

11 VEHICLES OPERATING ON CRAWLER TYPE TRACKS 40,000 pounds

12 TRUCKS EQUIPPED WITH SELFCOMPACTORS

13 OR ROLL-OFF HOISTS AND ROLL-OFF CONTAINERS FOR GARBAGE

14 OR REFUSE HAULS ONLY AND TRUCKS USED FOR

15 THE COLLECTION OF RENDERING MATERIALS

16 On Highway Not Part of National System

17 of Interstate and Defense Highways

18 with 2 axles 36,000 pounds

19 with 3 axles 54,000 pounds

20 TWO AXLE TRUCKS EQUIPPED WITH

21 A FRONT LOADING COMPACTOR USED EXCLUSIVELY

22 FOR THE COLLECTION OF GARBAGE, REFUSE, OR RECYCLING

23 with 2 axles 40,000 pounds

24 (c) Cities having a population of more than 50,000 may
25 permit by ordinance axle loads on 2 axle motor vehicles 33
26 1/2% above those provided for herein, but the increase shall
27 not become effective until the city has officially notified
28 the Department of the passage of the ordinance and shall not
29 apply to those vehicles when outside of the limits of the
30 city, nor shall the gross weight of any 2 axle motor vehicle
31 operating over any street of the city exceed 40,000 pounds.

32 (d) Weight limitations shall not apply to vehicles

1 (including loads) operated by a public utility when
2 transporting equipment required for emergency repair of
3 public utility facilities or properties or water wells.

4 A combination of vehicles, including a tow truck and a
5 disabled vehicle or disabled combination of vehicles, that
6 exceeds the weight restriction imposed by this Code, may be
7 operated on a public highway in this State provided that
8 neither the disabled vehicle nor any vehicle being towed nor
9 the tow truck itself shall exceed the weight limitations
10 permitted under this Chapter. During the towing operation,
11 neither the tow truck nor the vehicle combination shall
12 exceed 24,000 pounds on a single rear axle and 44,000 pounds
13 on a tandem rear axle, provided the towing vehicle:

14 (1) is specifically designed as a tow truck having
15 a gross vehicle weight rating of at least 18,000 pounds
16 and is equipped with air brakes, provided that air brakes
17 are required only if the towing vehicle is towing a
18 vehicle, semitrailer, or tractor-trailer combination that
19 is equipped with air brakes;

20 (2) is equipped with flashing, rotating, or
21 oscillating amber lights, visible for at least 500 feet
22 in all directions;

23 (3) is capable of utilizing the lighting and
24 braking systems of the disabled vehicle or combination of
25 vehicles; and

26 (4) does not engage in a tow exceeding 20 miles
27 from the initial point of wreck or disablement. Any
28 additional movement of the vehicles may occur only upon
29 issuance of authorization for that movement under the
30 provisions of Sections 15-301 through 15-319 of this
31 Code.

32 Gross weight limits shall not apply to the combination of
33 the tow truck and vehicles being towed. The tow truck
34 license plate must cover the operating empty weight of the

1 tow truck only. The weight of each vehicle being towed shall
2 be covered by a valid license plate issued to the owner or
3 operator of the vehicle being towed and displayed on that
4 vehicle. If no valid plate issued to the owner or operator of
5 that vehicle is displayed on that vehicle, or the plate
6 displayed on that vehicle does not cover the weight of the
7 vehicle, the weight of the vehicle shall be covered by the
8 third tow truck plate issued to the owner or operator of the
9 tow truck and temporarily affixed to the vehicle being towed.

10 The Department may by rule or regulation prescribe
11 additional requirements. However, nothing in this Code shall
12 prohibit a tow truck under instructions of a police officer
13 from legally clearing a disabled vehicle, that may be in
14 violation of weight limitations of this Chapter, from the
15 roadway to the berm or shoulder of the highway. If in the
16 opinion of the police officer that location is unsafe, the
17 officer is authorized to have the disabled vehicle towed to
18 the nearest place of safety.

19 For the purpose of this subsection, gross vehicle weight
20 rating, or GVWR, shall mean the value specified by the
21 manufacturer as the loaded weight of the tow truck.

22 (e) No vehicle or combination of vehicles equipped with
23 pneumatic tires shall be operated, unladen or with load, upon
24 the highways of this State in violation of the provisions of
25 any permit issued under the provisions of Sections 15-301
26 through 15-319 of this Chapter.

27 (f) On designated Class I, II, or III highways and the
28 National System of Interstate and Defense Highways, no
29 vehicle or combination of vehicles with pneumatic tires may
30 be operated, unladen or with load, when the total weight on
31 the road surface exceeds the following: 20,000 pounds on a
32 single axle; 34,000 pounds on a tandem axle with no axle
33 within the tandem exceeding 20,000 pounds; 80,000 pounds
34 gross weight for vehicle combinations of 5 or more axles; or

1 a total weight on a group of 2 or more consecutive axles in
 2 excess of that weight produced by the application of the
 3 following formula: $W = 500$ times the sum of (LN divided by
 4 $N-1) + 12N + 36$, where "W" equals overall total weight on any
 5 group of 2 or more consecutive axles to the nearest 500
 6 pounds, "L" equals the distance measured to the nearest foot
 7 between extremes of any group of 2 or more consecutive axles,
 8 and "N" equals the number of axles in the group under
 9 consideration.

10 The above formula when expressed in tabular form results
 11 in allowable loads as follows:

12	Distance measured					
13	to the nearest					
14	foot between the					
15	extremes of any		Maximum weight in pounds			
16	group of 2 or		of any group of			
17	more consecutive		2 or more consecutive axles			
18	axles					
19	feet	2 axles	3 axles	4 axles	5 axles	6 axles
20	4	34,000				
21	5	34,000				
22	6	34,000				
23	7	34,000				
24	8	38,000*	42,000			
25	9	39,000	42,500			
26	10	40,000	43,500			
27	11		44,000			
28	12		45,000	50,000		
29	13		45,500	50,500		
30	14		46,500	51,500		
31	15		47,000	52,000		
32	16		48,000	52,500	58,000	
33	17		48,500	53,500	58,500	
34	18		49,500	54,000	59,000	

1	19	50,000	54,500	60,000	
2	20	51,000	55,500	60,500	66,000
3	21	51,500	56,000	61,000	66,500
4	22	52,500	56,500	61,500	67,000
5	23	53,000	57,500	62,500	68,000
6	24	54,000	58,000	63,000	68,500
7	25	54,500	58,500	63,500	69,000
8	26	55,500	59,500	64,000	69,500
9	27	56,000	60,000	65,000	70,000
10	28	57,000	60,500	65,500	71,000
11	29	57,500	61,500	66,000	71,500
12	30	58,500	62,000	66,500	72,000
13	31	59,000	62,500	67,500	72,500
14	32	60,000	63,500	68,000	73,000
15	33		64,000	68,500	74,000
16	34		64,500	69,000	74,500
17	35		65,500	70,000	75,000
18	36		66,000	70,500	75,500
19	37		66,500	71,000	76,000
20	38		67,500	72,000	77,000
21	39		68,000	72,500	77,500
22	40		68,500	73,000	78,000
23	41		69,500	73,500	78,500
24	42		70,000	74,000	79,000
25	43		70,500	75,000	80,000
26	44		71,500	75,500	
27	45		72,000	76,000	
28	46		72,500	76,500	
29	47		73,500	77,500	
30	48		74,000	78,000	
31	49		74,500	78,500	
32	50		75,500	79,000	
33	51		76,000	80,000	
34	52		76,500		

1	53	77,500
2	54	78,000
3	55	78,500
4	56	79,500
5	57	80,000

6 *If the distance between 2 axles is 96 inches or less, the 2
7 axles are tandem axles and the maximum total weight may not
8 exceed 34,000 pounds, notwithstanding the higher limit
9 resulting from the application of the formula.

10 Vehicles not in a combination having more than 4 axles
11 may not exceed the weight in the table in this subsection (f)
12 for 4 axles measured between the extreme axles of the
13 vehicle.

14 Vehicles in a combination having more than 6 axles may
15 not exceed the weight in the table in this subsection (f) for
16 6 axles measured between the extreme axles of the
17 combination.

18 Local authorities and road district highway
19 commissioners, with respect to streets and highways under
20 their jurisdiction, without additional fees, may also by
21 ordinance or resolution allow the weight limitations of this
22 subsection, provided the maximum gross weight on any one axle
23 shall not exceed 20,000 pounds and the maximum total weight
24 on any tandem axle shall not exceed 34,000 pounds, on
25 designated highways when appropriate regulatory signs giving
26 notice are erected upon the street or highway or portion of
27 any street or highway affected by the ordinance or
28 resolution.

29 The following are exceptions to the above formula:

30 (1) Two consecutive sets of tandem axles may carry
31 a total weight of 34,000 pounds each if the overall
32 distance between the first and last axles of the
33 consecutive sets of tandem axles is 36 feet or more.

34 (2) Vehicles for which a different limit is

1 established and posted in accordance with Section 15-316
2 of this Code.

3 (3) Vehicles for which the Department of
4 Transportation and local authorities issue overweight
5 permits under authority of Section 15-301 of this Code.
6 These vehicles are not subject to the bridge formula.

7 (4) Tow trucks subject to the conditions provided
8 in subsection (d) may not exceed 24,000 pounds on a
9 single rear axle or 44,000 pounds on a tandem rear axle.

10 (5) A tandem axle on a 3-axle truck registered as a
11 Special Hauling Vehicle, manufactured prior to or in the
12 model year of 2014 2004, and registered in Illinois prior
13 to January 1, 2015 2005, with a distance between 2 axles
14 in a series greater than 72 inches but not more than 96
15 inches may not exceed a total weight of 36,000 pounds and
16 neither axle of the series may exceed 18,000 pounds.

17 (6) A truck not in combination, equipped with a
18 self compactor or an industrial roll-off hoist and
19 roll-off container, used exclusively for garbage or
20 refuse operations, may, when laden, transmit upon the
21 road surface, except when on part of the National System
22 of Interstate and Defense Highways, the following maximum
23 weights: 22,000 pounds on a single axle; 40,000 pounds on
24 a tandem axle; 36,000 pounds gross weight on a 2-axle
25 vehicle; 54,000 pounds gross weight on a 3-axle vehicle.
26 This vehicle is not subject to the bridge formula.

27 (7) Combinations of vehicles, registered as Special
28 Hauling Vehicles that include a semitrailer manufactured
29 prior to or in the model year of 2014 2004, and
30 registered in Illinois prior to January 1, 2015 2005,
31 having 5 axles with a distance of 42 feet or less between
32 extreme axles, may not exceed the following maximum
33 weights: 18,000 pounds on a single axle; 32,000 pounds on
34 a tandem axle; and 72,000 pounds gross weight. This

1 combination of vehicles is not subject to the bridge
2 formula. For all those combinations of vehicles that
3 include a semitrailer manufactured after the effective
4 date of this amendatory Act of the 92nd General Assembly,
5 the overall distance between the first and last axles of
6 the 2 sets of tandems must be 18 feet 6 inches or more.
7 Any combination of vehicles that has had its cargo
8 container replaced in its entirety after December 31,
9 2014 ~~2004~~ may not exceed the weights allowed by the
10 bridge formula.

11 No vehicle or combination of vehicles equipped with other
12 than pneumatic tires may be operated, unladen or with load,
13 upon the highways of this State when the gross weight on the
14 road surface through any wheel exceeds 800 pounds per inch
15 width of tire tread or when the gross weight on the road
16 surface through any axle exceeds 16,000 pounds.

17 (f-1) A vehicle and load not exceeding 73,280 pounds is
18 allowed access as follows:

19 (1) From any State designated highway onto any
20 county, township, or municipal highway for a distance of
21 5 highway miles for the purpose of loading and unloading,
22 provided:

23 (A) The vehicle and load does not exceed 8
24 feet 6 inches in width and 65 feet overall length.

25 (B) There is no sign prohibiting that access.

26 (C) The route is not being used as a
27 thoroughfare between State designated highways.

28 (2) From any State designated highway onto any
29 county or township highway for a distance of 5 highway
30 miles, or any municipal highway for a distance of one
31 highway mile for the purpose of food, fuel, repairs, and
32 rest, provided:

33 (A) The vehicle and load does not exceed 8
34 feet 6 inches in width and 65 feet overall length.

1 (B) There is no sign prohibiting that access.

2 (C) The route is not being used as a
3 thoroughfare between State designated highways.

4 (f-2) A vehicle and load greater than 73,280 pounds in
5 weight but not exceeding 80,000 pounds is allowed access as
6 follows:

7 (1) From a Class I highway onto any street or
8 highway for a distance of one highway mile for the
9 purpose of loading, unloading, food, fuel, repairs, and
10 rest, provided there is no sign prohibiting that access.

11 (2) From a Class I, II, or III highway onto any
12 State highway or any local designated highway for a
13 distance of 5 highway miles for the purpose of loading,
14 unloading, food, fuel, repairs, and rest.

15 Section 5-35 of the Illinois Administrative Procedure Act
16 relating to procedures for rulemaking shall not apply to the
17 designation of highways under this subsection.

18 (g) No person shall operate a vehicle or combination of
19 vehicles over a bridge or other elevated structure
20 constituting part of a highway with a gross weight that is
21 greater than the maximum weight permitted by the Department,
22 when the structure is sign posted as provided in this
23 Section.

24 (h) The Department upon request from any local authority
25 shall, or upon its own initiative may, conduct an
26 investigation of any bridge or other elevated structure
27 constituting a part of a highway, and if it finds that the
28 structure cannot with safety to itself withstand the weight
29 of vehicles otherwise permissible under this Code the
30 Department shall determine and declare the maximum weight of
31 vehicles that the structures can withstand, and shall cause
32 or permit suitable signs stating maximum weight to be erected
33 and maintained before each end of the structure. No person
34 shall operate a vehicle or combination of vehicles over any

1 structure with a gross weight that is greater than the posted
2 maximum weight.

3 (i) Upon the trial of any person charged with a
4 violation of subsections (g) or (h) of this Section, proof of
5 the determination of the maximum allowable weight by the
6 Department and the existence of the signs, constitutes
7 conclusive evidence of the maximum weight that can be
8 maintained with safety to the bridge or structure.

9 (Source: P.A. 92-417, eff. 1-1-02.)

10 Section 99. Effective date. This Act takes effect
11 January 1, 2004.