

99TH GENERAL ASSEMBLY State of Illinois 2015 and 2016 HB6093

Introduced 2/11/2016, by Rep. Joe Sosnowski

SYNOPSIS AS INTRODUCED:

625 ILCS 5/1-105.2a new
625 ILCS 5/1-105.7 new
625 ILCS 5/1-198 from Ch. 95 1/2, par. 1-198
625 ILCS 5/1-212 from Ch. 95 1/2, par. 1-212
625 ILCS 5/15-107 from Ch. 95 1/2, par. 15-107

Amends the Illinois Vehicle Code. Provides a definition for "automobile transporter" and "backhaul." Amends the definition for "stinger-steered semitrailer" and "truck tractor." Provides that the length of a stinger-steered semitrailer specifically designed to transport motor vehicles or an automobile transporter cannot exceed 80 feet (as opposed to 75 feet), with an overhang of less than 4 feet (as opposed to 3 feet) and a rear overhang of less than 6 feet (as opposed to 4 feet). Provides an automobile transporter of these lengths can also be used when transporting other cargo or general freight on a backhaul. Effective immediately.

LRB099 17002 AXK 41354 b

1 AN ACT concerning transportation.

Be it enacted by the People of the State of Illinois, represented in the General Assembly:

- 4 Section 5. The Illinois Vehicle Code is amended by changing
- 5 Sections 1-198, 1-212, and 15-107 and by adding Sections
- 6 1-105.2a and 1-105.7 as follows:
- 7 (625 ILCS 5/1-105.2a new)
- 8 Sec. 1-105.2a. Automobile transporter. Any vehicle
- 9 combination designed and used for the transport of assembled
- 10 vehicles, including truck camper units, and includes its use
- when transporting other cargo or general freight on a backhaul
- 12 while in compliance with the weight limitations for a truck
- 13 <u>tractor and semitrailer combination.</u>
- 14 (625 ILCS 5/1-105.7 new)
- Sec. 1-105.7. Backhaul. The return trip of a vehicle
- 16 transporting cargo or general freight, especially when
- 17 carrying goods back over all or part of the same route.
- 18 (625 ILCS 5/1-198) (from Ch. 95 1/2, par. 1-198)
- 19 Sec. 1-198. Stinger-steered semitrailer.
- 20 Every semitrailer, including automobile transporters,
- 21 which has its kingpin on a projection to the front of the

- 1 structure of such semitrailer and is combined with the 5th
- 2 wheel of the truck tractor at a point not less than two feet to
- 3 the rear of the center of the rearmost axle of such tractor.
- 4 (Source: P.A. 76-1586.)
- 5 (625 ILCS 5/1-212) (from Ch. 95 1/2, par. 1-212)
- 6 Sec. 1-212. Truck tractor.
- 7 Every motor vehicle designed and used primarily for drawing
- 8 other vehicles and not so constructed as to carry a load other
- 9 than a part of the weight of the vehicle and load so drawn, or a
- 10 power unit that carries as property motor vehicles when
- 11 operating in combination with a semitrailer in transporting
- 12 motor vehicles or any other commodity, including cargo or
- 13 general freight, on a backhaul.
- 14 (Source: P.A. 76-1586.)
- 15 (625 ILCS 5/15-107) (from Ch. 95 1/2, par. 15-107)
- Sec. 15-107. Length of vehicles.
- 17 (a) The maximum length of a single vehicle on any highway
- 18 of this State may not exceed 42 feet except the following:
- 19 (1) Semitrailers.
- 20 (2) Charter or regulated route buses may be up to 45
- feet in length, not including energy absorbing bumpers.
- (a-1) A motor home as defined in Section 1-145.01 may be up
- 23 to 45 feet in length, not including energy absorbing bumpers.
- 24 The length limitations described in this subsection (a-1) shall

- 1 be exclusive of energy-absorbing bumpers and rear view mirrors.
- 2 (b) On all non-State highways, the maximum length of vehicles in combinations is as follows:
 - (1) A truck tractor in combination with a semitrailer may not exceed 55 feet overall dimension.
 - (2) A truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer may not exceed 60 feet overall dimension.
 - (3) Combinations specially designed to transport motor vehicles or boats may not exceed 60 feet overall dimension.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismembered are exempt from length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both

13

14

15

16

17

18

19

20

21

22

23

24

25

- sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.
- A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.
- 7 All other combinations not listed in this subsection (b) 8 may not exceed 60 feet overall dimension.
- 9 (c) Except as provided in subsections (c-1) and (c-2),
 10 combinations of vehicles may not exceed a total of 2 vehicles
 11 except the following:
 - (1) A truck tractor semitrailer may draw one trailer.
 - (2) A truck tractor semitrailer may draw one converter dolly or one semitrailer.
 - (3) A truck tractor semitrailer may draw one vehicle that is defined in Chapter 1 as special mobile equipment, provided the overall dimension does not exceed 60 feet.
 - (4) A truck in transit may draw 3 trucks in transit coupled together by the triple saddlemount method.
 - (5) Recreational vehicles consisting of 3 vehicles, provided the following:
 - (A) The total overall dimension does not exceed 60 feet.
 - (B) The towing vehicle is a properly registered vehicle capable of towing another vehicle using a fifth-wheel type assembly.

- (C) The second vehicle in the combination of vehicles is a recreational vehicle that is towed by a fifth-wheel assembly. This vehicle must be properly registered and must be equipped with brakes, regardless of weight.
 - (D) The third vehicle must be the lightest of the 3 vehicles and be a trailer or semitrailer designed or used for transporting a boat, all-terrain vehicle, personal watercraft, or motorcycle.
 - (E) The towed vehicles may be only for the use of the operator of the towing vehicle.
 - (F) All vehicles must be properly equipped with operating brakes and safety equipment required by this Code, except the additional brake requirement in subdivision (C) of this subparagraph (5).
 - (6) A tow truck in combination with a disabled vehicle or combination of disabled vehicles, provided the towing vehicle:
 - (A) Is specifically designed as a tow truck having a gross vehicle weight rating of at least 18,000 pounds and equipped with air brakes, provided that air brakes are required only if the towing vehicle is towing a vehicle, semitrailer, or tractor-trailer combination that is equipped with air brakes. For the purpose of this subsection, gross vehicle weight rating, or GVWR, means the value specified by the manufacturer as the

- 1 loaded weight of the tow truck.
 - (B) Is equipped with flashing, rotating, or oscillating amber lights, visible for at least 500 feet in all directions.
 - (C) Is capable of utilizing the lighting and braking systems of the disabled vehicle or combination of vehicles.
 - (D) Does not engage a tow exceeding 50 highway miles from the initial point of wreck or disablement to a place of repair. Any additional movement of the vehicles may occur only upon issuance of authorization for that movement under the provisions of Sections 15-301 through 15-319 of this Code.

The Department may by rule or regulation prescribe additional requirements regarding length limitations for a tow truck towing another vehicle.

For purposes of this Section, a tow-dolly that merely serves as substitute wheels for another legally licensed vehicle is considered part of the licensed vehicle and not a separate vehicle.

- (7) Commercial vehicles consisting of 3 vehicles, provided the following:
- (A) The total overall dimension does not exceed 65 feet.
 - (B) The towing vehicle is a properly registered vehicle capable of towing another vehicle using a

26

vehicles if:

1	fifth-wheel type assembly or a goose-neck hitch ball.
2	(C) The third vehicle must be the lightest of the 3
3	vehicles and be a trailer or semitrailer.
4	(D) All vehicles must be properly equipped with
5	operating brakes and safety equipment required by this
6	Code.
7	(E) The combination of vehicles must be operated by
8	a person who holds a commercial driver's license (CDL).
9	(F) The combination of vehicles must be en route to
10	a location where new or used trailers are sold by an
11	Illinois or out-of-state licensed new or used trailer
12	dealer.
13	(c-1) A combination of 3 vehicles is allowed access to any
14	State designated highway if:
15	(1) the length of neither towed vehicle exceeds 28.5
16	feet;
17	(2) the overall wheel base of the combination of
18	vehicles does not exceed 62 feet; and
19	(3) the combination of vehicles is en route to a
20	location where new or used trailers are sold by an Illinois
21	or out-of-state licensed new or used trailer dealer.
22	(c-2) A combination of 3 vehicles is allowed access from
23	any State designated highway onto any county, township, or
24	municipal highway for a distance of 5 highway miles for the

purpose of delivery or collection of one or both of the towed

- 1 (1) the length of neither towed vehicle exceeds 28.5 feet;
 - (2) the combination of vehicles does not exceed 40,000 pounds in gross weight and 8 feet 6 inches in width;
 - (3) there is no sign prohibiting that access;
 - (4) the route is not being used as a thoroughfare between State designated highways; and
 - (5) the combination of vehicles is en route to a location where new or used trailers are sold by an Illinois or out-of-state licensed new or used trailer dealer.
 - (d) On Class I highways there are no overall length limitations on motor vehicles operating in combinations provided:
 - (1) The length of a semitrailer, unladen or with load, in combination with a truck tractor may not exceed 53 feet.
 - (2) The distance between the kingpin and the center of the rear axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 45 feet 6 inches. The limit contained in this paragraph (2) shall not apply to trailers or semi-trailers used for the transport of livestock as defined by Section 18b-101.
 - (3) The length of a semitrailer or trailer, unladen or with load, operated in a truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination, may not exceed 28 feet 6 inches.
 - (4) Maxi-cube combinations, as defined in Chapter 1,

may not exceed 65 feet overall dimension.

- (5) Combinations of vehicles specifically designed to transport motor vehicles or boats may not exceed 65 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
- (6) Stinger steered semitrailer vehicles as defined in Chapter 1, specifically designed to transport motor vehicles or boats and automobile transporters, as defined in Chapter 1, may not exceed 80 75 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
- (7) A truck in transit transporting 3 trucks coupled together by the triple saddlemount method may not exceed 75 feet overall dimension.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismembered are exempt from length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day;

11

12

13

14

15

16

17

18

19

20

21

22

- Memorial Day; Independence Day; Labor Day; Thanksgiving Day;
 and Christmas Day.
- Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.
 - A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.
 - The length limitations described in this paragraph (d) shall be exclusive of safety and energy conservation devices, such as bumpers, refrigeration units or air compressors and other devices, that the Department may interpret as necessary for safe and efficient operation; except that no device excluded under this paragraph shall have by its design or use the capability to carry cargo.
 - Section 5-35 of the Illinois Administrative Procedure Act relating to procedures for rulemaking shall not apply to the designation of highways under this paragraph (d).
- (e) On Class II highways there are no overall length limitations on motor vehicles operating in combinations, provided:

- (1) The length of a semitrailer, unladen or with load, in combination with a truck tractor, may not exceed 53 feet overall dimension.
 - (2) The distance between the kingpin and the center of the rear axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 45 feet 6 inches. The limit contained in this paragraph (2) shall not apply to trailers or semi-trailers used for the transport of livestock as defined by Section 18b-101.
 - (3) A truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination may not exceed 65 feet in dimension from front axle to rear axle.
 - (4) The length of a semitrailer or trailer, unladen or with load, operated in a truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination, may not exceed 28 feet 6 inches.
 - (5) Maxi-cube combinations, as defined in Chapter 1, may not exceed 65 feet overall dimension.
 - (6) A combination of vehicles, specifically designed to transport motor vehicles or boats, may not exceed 65 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
 - (7) Stinger steered semitrailer vehicles, as defined in Chapter 1, specifically designed to transport motor

vehicles or boats <u>and automobile transporters</u>, <u>as defined</u>

in Chapter 1, may not exceed <u>80</u> 75 feet overall dimension.

The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.

(8) A truck in transit transporting 3 trucks coupled together by the triple saddlemount method may not exceed 75 feet overall dimension.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismembered are exempt from length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.

1	A t	ow truc	ck in	combina	ation w	ith a	disabled	vehicle	or
2	combina	tion of	disabl	led vehi	cles, a	s provi	ided in pa	aragraph	(6)
3	of subs	section	(c) c	of this	Sectio	on, is	exempt	from ler	ıgth
4	limitat	ions.							

Local authorities, with respect to streets and highways under their jurisdiction, may also by ordinance or resolution allow length limitations of this subsection (e).

The length limitations described in this paragraph (e) shall be exclusive of safety and energy conservation devices, such as bumpers, refrigeration units or air compressors and other devices, that the Department may interpret as necessary for safe and efficient operation; except that no device excluded under this paragraph shall have by its design or use the capability to carry cargo.

Section 5-35 of the Illinois Administrative Procedure Act relating to procedures for rulemaking shall not apply to the designation of highways under this paragraph (e).

- (e-1) Combinations of vehicles not exceeding 65 feet overall length are allowed access as follows:
 - (1) From any State designated highway onto any county, township, or municipal highway for a distance of 5 highway miles for the purpose of loading and unloading, provided:
- (A) The vehicle does not exceed 80,000 pounds in gross weight and 8 feet 6 inches in width.
 - (B) There is no sign prohibiting that access.
 - (C) The route is not being used as a thoroughfare

3

4

6

7

8

9

12

13

14

15

16

17

18

19

20

21

22

23

1 between State designated highways.

- (2) From any State designated highway onto any county or township highway for a distance of 5 highway miles or onto any municipal highway for a distance of one highway mile for the purpose of food, fuel, repairs, and rest, provided:
 - (A) The vehicle does not exceed 80,000 pounds in gross weight and 8 feet 6 inches in width.
 - (B) There is no sign prohibiting that access.
- 10 (C) The route is not being used as a thoroughfare
 11 between State designated highways.
 - (e-2) Except as provided in subsection (e-3), combinations of vehicles over 65 feet in length, with no overall length limitation except as provided in subsections (d) and (e) of this Section, are allowed access as follows:
 - (1) From a Class I highway onto any street or highway for a distance of one highway mile for the purpose of loading, unloading, food, fuel, repairs, and rest, provided there is no sign prohibiting that access.
 - (2) From a Class I or Class II highway onto any State highway or any locally designated highway for a distance of 5 highway miles for the purpose of loading, unloading, food, fuel, repairs, and rest.
- 24 (e-3) Combinations of vehicles over 65 feet in length 25 operated by household goods carriers, with no overall length 26 limitations except as provided in subsections (d) and (e) of

- this Section, have unlimited access to points of loading and unloading.
- 3 (f) On Class III and other non-designated State highways,
 4 the length limitations for vehicles in combination are as
 5 follows:
 - (1) Truck tractor-semitrailer combinations, must comply with either a maximum 55 feet overall wheel base or a maximum 65 feet extreme overall dimension.
 - (2) Semitrailers, unladen or with load, may not exceed 53 feet overall dimension.
 - (3) No truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination may exceed 60 feet extreme overall dimension.
 - (4) The distance between the kingpin and the center axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 42 feet 6 inches. The limit contained in this paragraph (4) shall not apply to trailers or semi-trailers used for the transport of livestock as defined by Section 18b-101.
 - (g) Length limitations in the preceding subsections of this Section 15-107 do not apply to the following:
 - (1) Vehicles operated in the daytime, except on Saturdays, Sundays, or legal holidays, when transporting poles, pipe, machinery, or other objects of a structural nature that cannot readily be dismembered, provided the overall length of vehicle and load may not exceed 100 feet

and no object exceeding 80 feet in length may be transported unless a permit has been obtained as authorized in Section 15-301.

- (2) Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties, but during night operation every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps upon the extreme ends of any projecting load to clearly mark the dimensions of the load.
- (3) A tow truck in combination with a disabled vehicle or combination of disabled vehicles, provided the towing vehicle meets the following conditions:
 - (A) It is specifically designed as a tow truck having a gross vehicle weight rating of at least 18,000 pounds and equipped with air brakes, provided that air brakes are required only if the towing vehicle is towing a vehicle, semitrailer, or tractor-trailer combination that is equipped with air brakes.
 - (B) It is equipped with flashing, rotating, or oscillating amber lights, visible for at least 500 feet in all directions.
 - (C) It is capable of utilizing the lighting and braking systems of the disabled vehicle or combination of vehicles.
 - (D) It does not engage in a tow exceeding 50 miles

from the initial point of wreck or disablement.

The Department may by rule or regulation prescribe additional requirements regarding length limitations for a tow truck towing another vehicle. The towing vehicle, however, may tow any disabled vehicle from the initial point of wreck or disablement to a point where repairs are actually to occur. This movement shall be valid only on State routes. The tower must abide by posted bridge weight limits.

For the purpose of this subsection, gross vehicle weight rating, or GVWR, shall mean the value specified by the manufacturer as the loaded weight of the tow truck. Legal holidays referred to in this Section shall be specified as the day on which the following traditional holidays are celebrated:

- 14 New Year's Day;
- 15 Memorial Day;
- 16 Independence Day;
- 17 Labor Day;
- 18 Thanksgiving Day; and
- 19 Christmas Day.
 - (h) The load upon any vehicle operated alone, or the load upon the front vehicle of a combination of vehicles, shall not extend more than 3 feet beyond the front wheels of the vehicle or the front bumper of the vehicle if it is equipped with a front bumper. The provisions of this subsection (h) shall not apply to any vehicle or combination of vehicles specifically designed for the collection and transportation of waste,

- garbage, or recyclable materials during the vehicle's operation in the course of collecting garbage, waste, or recyclable materials if the vehicle is traveling at a speed not in excess of 15 miles per hour during the vehicle's operation and in the course of collecting garbage, waste, or recyclable materials. However, in no instance shall the load extend more than 7 feet beyond the front wheels of the vehicle or the front bumper of the vehicle if it is equipped with a front bumper.
 - (i) The load upon the front vehicle of an automobile transporter or a stinger-steered vehicle a combination of vehicles specifically designed to transport motor vehicles shall not extend more than 4 3 feet beyond the foremost part of the transporting vehicle and the load upon the rear transporting vehicle shall not extend more than 6 4 feet beyond the rear of the bed or body of the vehicle. This paragraph shall only be applicable upon highways designated in paragraphs (d) and (e) of this Section.
 - (j) Articulated vehicles comprised of 2 sections, neither of which exceeds a length of 42 feet, designed for the carrying of more than 10 persons, may be up to 60 feet in length, not including energy absorbing bumpers, provided that the vehicles are:
 - 1. operated by or for any public body or motor carrier authorized by law to provide public transportation services; or
 - 2. operated in local public transportation service by

- any other person and the municipality in which the service
- is to be provided approved the operation of the vehicle.
- (j-1) (Blank).
- 4 (k) Any person who is convicted of violating this Section
- 5 is subject to the penalty as provided in paragraph (b) of
- 6 Section 15-113.
- 7 (1) (Blank).
- 8 (Source: P.A. 96-34, eff. 1-1-10; 96-37, eff. 7-13-09; 96-1352,
- 9 eff. 7-28-10; 97-200, eff. 7-27-11; 97-883, eff. 1-1-13.)
- 10 Section 99. Effective date. This Act takes effect upon
- 11 becoming law.